

Product data sheet

IQ lock M *



Mechanical panic lock for simple panic functions on single leaf doors

AREAS OF APPLICATION

- Single leaf emergency exit and panic doors
- Doors along escape and rescue routes
- Fire and smoke protection doors

PRODUCT FEATURES

- Mechanical self-locking ensures automatic crossbar projection every time the door is closed
- Panic function which opens (even locked) emergency exits in the direction of escape
- Divided cross latch prevents the bolt from locking even under side-load
- Small rear backset and small dimensions of the lock case
- Can be combined with electronic thumbturn cylinders

TECHNICAL DATA

Productname	IQ lock M *
DIN direction	left / right
Service temperature	-10 - 50 °C
Panic function / mechanical self-locking	Yes
Divided cross latch (3 mm gap between latch and bolt)	Yes
Power consumption	N/A, N/A
Resistant to forcing	10000 N

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Distance lock	Backset	DIN direction
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	110195	72 mm	100 mm	left / right
IQ lock M	for tubular-framed doors with rectangular face plate 24 x 285 x 3 mm	161353	92 mm	40 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	114611	78 mm	100 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	114651	78 mm	70 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	110192	72 mm	55 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	115016	92 mm	40 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	114606	94 mm	40 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	114647	94 mm	35 mm	left / right
IQ lock M *	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	114649	94 mm	45 mm	left / right
IQ lock M	for tubular-framed doors with rectangular face plate 24 x 285 x 3 mm	161354	92 mm	45 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	114607	94 mm	45 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	110193	72 mm	65 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 28 x 270 x 3 mm	162618	92 mm	35 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	114648	94 mm	40 mm	left / right

IQ lock M *

Designation	Description	Ident-No.	Distance lock	Backset	DIN direction
IQ lock M	for tubular-framed doors / with rectangular face plate 22 x 285 x 3 mm	157376	92 mm	45 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 24 x 235 x 3 mm	163833	72 mm	65 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	103603	92 mm	35 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 22 x 285 x 3 mm	163344	92 mm	40 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	114604	94 mm	35 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 24 x 270 x 3 mm	110191	92 mm	45 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	110194	72 mm	80 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 28 x 270 x 3 mm	162619	92 mm	40 mm	left / right
IQ lock M	for tubular-framed doors / with rectangular face plate 22 x 285 x 3 mm	157375	92 mm	35 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	114653	78 mm	100 mm	left / right
IQ lock M *	for tubular-framed doors / with rectangular face plate 28 x 270 x 3 mm	162620	92 mm	45 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	114652	78 mm	80 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	114609	78 mm	70 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 24 x 235 x 3 mm	163832	72 mm	80 mm	left / right
IQ lock M	for solid leaf doors / with round face plate 20 x 235 x 3 mm	114610	78 mm	80 mm	left / right
IQ lock M	for tubular-framed doors with rectangular face plate 24 x 285 x 3 mm	161342	92 mm	35 mm	left / right

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.