

Product data sheet

ECturn



Electromechanical swing door drive for accessible single leaf doors weighing up to 125 kg

AREAS OF APPLICATION

- Single-action, single leaf, right and left closing doors
- Single-action doors up to 1100 mm leaf width or 125 kg weight
- Entrance and interior doors with moderate access frequency
- Automation of frameless all-glass doors
- Door leaf installation and transom installation
- Barrier-free access

PRODUCT FEATURES

- Opening and closing speed can be individually adjusted
- Electrical latching action which accelerates the door shortly before the closed position
- Low-energy function opens and closes the door with reduced speed, fulfilling the highest safety demands
- Obstacle detection detects an object through contact and stops the opening or closing process
- Automatic reversing detects an obstacle and returns to the opening position
- Push & Go function triggers the automatic drive following light manual pressure on the door leaf
- Drive can be used with guide rail or link arm
- Glass guide rail available for use on glass doors with a glass thickness of 8-10 mm
- Optional rechargeable battery provides maximum safety during a power failure
- Optional radio reception board for wireless activation by radio transmitter

TECHNICAL DATA

Productname	ECturn
Height	60 mm
Depth	60 mm
Leaf weight (max.) 1-leaf	125 kg
Leaf width (min.-max.)	650 mm - 1100 mm
Reveal depth (max.)	200 mm
Door overlap (max.)	50 mm
Drive type	Electromechanical
Opening angle (max.)	110 °
DIN left	Yes
DIN right	Yes



Transom installation opposite hinge side with link arm	Yes
Transom installation opposite hinge side with guide rail	Yes
Transom installation hinge side with guide rail	Yes
Transom installation opposite hinge side with guide rail on all-glass doors	Yes
Transom installation hinge side with guide rail on all-glass doors	Yes
Door leaf installation opposite hinge side with guide rail	Yes
Door leaf installation hinge side with guide rail	Yes
Door leaf installation hinge side with link arm	Yes
Electrical latching action	Yes
Disconnection from mains	Main switch in the drive
Activation delay (max.)	10 s
Operating voltage	110 – 230 V
Power rating	75 W
Power supply for external consumers (24 V DC)	600 mA
Service temperature	-15 – 50 °C
IP rating	IP20
Mode of operation	Off, Automatic, Permanently open, Night
Type of function	Fully automatic
Automatic function	Yes
Low-energy function	Yes
function smart swing	No
Key function	Yes
Obstacle detection	Yes
Automatic reversing	Yes
Push & Go	adjustable
Operation	Programme switch TPS, Programme switch integrated in the drive
Parameter setting	Programme switch DPS, Control unit
Standard conformity	EN 16005
Smoke switch integrated	No

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Supply voltage	Leaf width (min.)	Leaf width (max.)
Ecturn	Electromechanical swing door drive for 1-leaf single-action doors	134536	110 – 230 V	650 mm	1100 mm

ACCESSORIES**LINK ARM ECTURN**

For transom installation on opposite hinge side or door leaf
installation on hinge side for reveal depths of 0 - 200 mm



Designation	Description	Ident-No.	Colour
Link arm Ecturn	for reveal depth 90-200 mm	134664	silver-coloured
Link arm Ecturn	for reveal depth 0-100 mm	134663	silver-coloured
Link arm Ecturn *	for reveal depth 90-200 mm	135933	according to RAL
Link arm Ecturn	for reveal depth 0-100 mm	135932	according to RAL

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.