

Product data sheet Strike box tubular frame doors, long *



Mechanical strike box as passive leaf rod locking element on double leaf doors

AREAS OF APPLICATION

- → Passive leaf locking element (rod locking) on double leaf tubular-framed doors
- → Use of safety fittings possible
- ightarrow Location for vertical rods from above and below
- → Can be used on fire protection doors
- ightarrow Automated passive leaf unlocking possible through combination with IQ AUT

Strike box tubular frame doors, long * GEZ



PRODUCT FEATURES

- → Mechanical self-locking via top lock
- → Unlocking of active leaf via passive leaf door fitting (full panic function)

TECHNICAL DATA

| Productname | Strike box tubular frame doors, long * |
|---------------|--|
| DIN direction | left / right |

VARIANTS / ORDER INFO

| Designation | Description | Ident- No. | DIN direction | Backset |
|---|--|---------------|------------------|---------|
| Strike box tubular- framed doors, long * | without face plate, / for the use of / safety fittings / Distance of the screw points for locking bolts: 323 mm / the vertical locking bolts are positioned on backset | 133899 | left / right | 35 mm |
| Strike box tubular- framed doors, long * | without face plate, / for the use of / safety fittings / Distance of the screw points for locking bolts: 323 mm / the vertical locking bolts are positioned on backset | 133900 | left / right | 40 mm |
| Strike box tubular- framed doors, long * | without face plate, / for the use of / safety fittings / Distance of the screw points for locking bolts: 323 mm / the vertical locking bolts are positioned on backset | 133902 | left / right | 55 mm |
| Strike box tubular- framed doors, long * | without face plate, / for the use of / safety fittings / Distance of the screw points for locking bolts: 323 mm / the vertical locking bolts are positioned on backset | 133901 | left / right | 45 mm |

GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com

^{*} The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.