

Product data sheet TS wood complete package *



Overhead door closer with guide rail for single leaf doors up to 950 mm leaf width

AREAS OF APPLICATION

- ightarrow Fire and smoke protection doors
- ightarrow Right and left single-action doors
- ightarrow Single-action doors up to 950 mm leaf width
- ightarrow Door leaf and transom installation on the hinge and opposite hinge side



PRODUCT FEATURES

- ightarrow Hydraulic latching action which accelerates the door shortly before it is closed
- ightarrow Closing speed can be individually adjusted
- ightarrow All functions can be set from the front (except for closing force)
- ightarrow Door closer, can be used for right and left hand doors
- ightarrow Door closer, can be used for leaf and transom installation

TECHNICAL DATA

Productname	TS wood complete package *		
Closing force in accordance with EN 1154	EN 3		
Leaf width (max.)	950 mm		
Opening angle (max.)	180 °		
Identical design for DIN left and DIN right	Yes		
Standard conformity	EN 1154:1996/A1:2002/AC:2006		
Suitability for fire protection doors	Yes		
Length	226 mm		
Width	46 mm		
Height	60 mm		
Closing force adjustable	No		
Adjustable closing speed	Yes		
Latching action adjustable	Yes, via valve		
Back check integrated	No		
Safety valve againts overload	Yes		
Thermo-control valves	Yes		
Hold-open function	Optional		
Smoke switch integrated	No		

VARIANTS / ORDER INFO

Designati on	Description	ldent- No.	Colour	Closing force in accordance with EN 1154	Dimensions
TS Wood *	Overhead door closer with guide rail for single leaf doors up to 950 mm leaf width	131190	white RAL 9010	EN 3	226 x 46 x 60 mm
TS Wood *	Overhead door closer with guide rail for single leaf doors up to 950 mm leaf width	118431	silver- coloured	EN 3	226 x 46 x 60 mm
TS Wood *	Overhead door closer with guide rail for single leaf doors up to 950 mm leaf width	131188	white RAL 9016	EN 3	226 x 46 x 60 mm
TS Wood *	Overhead door closer with guide rail for single leaf doors up to 950 mm leaf width	131189	black RAL 9005	EN 3	226 x 46 x 60 mm



ACCESSORIES

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, curved shape

Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer *	for TS 3000/TS 2000, semi-radial, can only be used for door leaf installation	092928	Polished stainless steel	277 x 54 x 72 mm
Cover cap door closer *	for TS 3000/TS 2000, semi-radial, can only be used for door leaf installation	092929	Satin stainless steel	277 x 54 x 72 mm

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, rectangular shape

Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer *	for TS 3000 / TS 2000, square, can only be used for door leaf installation	092924	Satin stainless steel	237 x 54 x 72 mm
Cover cap door closer *	for TS 3000 / TS 2000, square, can only be used for door leaf installation	092923	Polished stainless steel	237 x 54 x 72 mm

COVER CAP DOOR CLOSER *

For TS 3000/TS 2000, can only be used for door leaf installation



Designation	Description	Ident-No.	Colour	Dimensions
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	072769	Stainless steel	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	072770	Brass	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	013487	silver-coloured	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	014855	white RAL 9016	237 x 55 x 67.2 mm
Cover cap door closer *	for TS 3000 / TS 2000, can only be used for door leaf installation	014849	dark bronze	237 x 55 x 67.2 mm
Cover cap door closer	for TS 3000 / TS 2000, can only be used for door leaf installation	014856	according to RAL	237 x 55 x 67.2 mm

Product data sheet | Page 4 of 4 TS wood complete package *

MECHANICAL HOLD-OPEN UNIT

FLEXIBLE OPENING RESTRICTOR

Designation

Designation

unit

Mechanical hold-open

Boxer 20.7 mm guide rail

For standard/T-Stop/Boxer 20.7 mm guide rail

Description

and off, can be overridden

for riveted guide rail, standard guide rail BG, standard guide rail and

Description

Flexible opening restrictor for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail

for standard / T-Stop / Boxer 20.7 mm guide rail, retention force adjustable, can be switched on 071924

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.



Ident-No.

Ident-No.

069780



